

Data Management and Automation at the APS

2013 Three-Way Meeting1 August 2013

Nicholas Schwarz

Principal Computer Scientist / Group Leader

Software Services Group

APS Engineering Support Division (AES)


Advanced Photon Source (APS)



Increasing Amounts and Complexity of Data

Detectors








Experiment Automation





Techniques





Fast Micro-Tomography





Keith Chang (Penn State College of Medicine)

Beamline and Detector

- 2-BM
- pco.dimax (36GB of onboard RAM)
- 2K X 2K @ 16-bits


Tomography Dataset


- Projections around 180 degrees
- ~1,500 FPS
- A few seconds of data collection
- ~1 minute readout
- Up to 11GB raw data per minute

Reconstruction

- Takes ~5 minutes
- Reconstructed data ~22GB

X-ray Photon Correlation Spectroscopy





Beamline

- 8-ID
- Kinetics measurements

XPCS Data


- 2D images over time
- A few minutes to collect
- Varies from 0.5GB to 50GB

Reduction

Multi-tau autocorrelation

APS Average Data Rate

Cumulative typical data volume at present: 112 TB/month Cumulative maximum data volume: 368 TB/month



F. De Carlo (ANL)



Increasing User Base









Goals / Constraints


Goals

- Store detector data temporarily
- Reduce (analyze) data after acquisition
- Keep data for some moderate amount of time
- Facilitate ability of users to take their data home

Constraints

- Acquisition must be as robust as possible
- Institution policy (e.g. firewalls, ownership, etc.)

Architecture



Workflow Pipeline




- Series of actors connected by message queues
- Stage
 - Acquisition
 - Run data analysis
 - Transfer files
 - Many languages: C++, Java, Python
- Message queues
 - Pass messages from one actor to the next
 - JMS message queues (ActiveMQ)


Pipeline Stages

Stages are composed of two separate classes:

- Director
 - interface with the message broker
- Actor
 - run scan / analysis / file transfer
 - save results
 - report status



Director



- Broker interface
- Handle job messages
- Control messages

- Update history
- Maintain provenance
- Execute Actor


Actor

Actor

- Called by Director
- Abstract interface for concrete implementation
- Execute job / analysis
- Report status


Analysis

- External application
- Internal code
- Read input data from HDF5
- Write output data to HDF5






Use Case: XPCS



Use Case: Tomography



User Access to Data




Globus Online

- Provides access to APS data from the outside
- Used by many user facilities and supercomputing centers
- Optimized bandwidth utilization for faster transfers
- www.globusonline.org



Globus Online




User / Scientist Perspective


Publication

- Multiple figures
- Different types of data





Laboratory Microscope Data



Synchrotron Derived Data

User / Scientist Perspective


















Even a single figure with synchrotron data may have data from multiple facilities.




Normalize Intensity Cell Finding Algorithm Data Fusion




Synchrotron Derived Data

Process of analyzing data generates new knowledge and data (and metadata).

Globus Online Catalog



Globus Online Catalog



Acknowledgements

The submitted manuscript has been created by UChicago Argonne, LLC, Operator of Argonne National Laboratory ("Argonne"). Argonne, a U.S. Department of Energy Office of Science laboratory, is operated under Contract No. DE-AC02-06CH11357. The U.S. Government retains for itself, and others acting on its behalf, a paid-up nonexclusive, irrevocable worldwide license in said article to reproduce, prepare derivative works, distribute copies to the public, and perform publicly and display publicly, by or on behalf of the Government.

This work is supported by the U.S. Department of Energy, Basic Energy Sciences, Office of Science, under contract # DE-AC02-06CH11357.

Thank you!

